



Bona Blocker

PRIMER ADDITIVE

Reduce bleed from knots and tannins.



Additive for reducing bleeding from natural wood substances and particularly extracts from wood knots and tannins from white oak. Reduces risk of yellow stains developing in white treated wood floors. For use with Bona White and Bona Natural Primer. One bottle of Bona Blocker is enough for two 5 litre cans of lacquer.

- Reduces knot bleeding

TECHNICAL DATA

Type of lacquer:	Isocyanate prepolymer
Mixing ratio:	1 part Bona Blocker to 20 parts Bona White or Bona Natural Primer (250 ml to a full 5 litre can)
Pot life:	3 hours at 20°C
Safety:	Classified, see safety data sheet for more details.
Cleaning:	Bona Cleaning Wipes, Bona S100, acetone, ethanol. Hardened product can only be removed mechanically.
Shelf life:	18 months from date of production in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +30°C during storage or transport
Disposal:	Waste and emptied containers should be handled in accordance with local regulations.
Pack size:	500ml bottle. 15 per box.

Additional detailed information is noted in the appropriate Safety Data Sheet.



Bona Blocker

PRIMER ADDITIVE

Reduce bleed from knots and tannins.

DIRECTIONS FOR USE

Ensure additive and primer are brought to room temperature before use.

- 1) Calculate how much primer you will need to treat the space in question. Shake the primer can and pour the required amount into another container. Note that after adding the Blocker, the mixed material must be used within three hours. Mixed material cannot be reused.
- 2) Add 5% Bona Blocker (250 ml to a full 5 lt. can) and shake the can forcefully for 60 seconds. Let the mixed material rest for five minutes.
- 3) Use the mixed material as normal and per separate instruction for Bona White or Bona Natural Primer. The blocking properties improve further if adding the Bona Blocker in the first two coats of primer.

IMPORTANT

Bona Blocker should only be used in combination with Bona White or Bona Natural Primer. Compatibility issues can occur with other Bona primers and topcoats.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and extensive testing but makes no claim to be complete. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice from Bona before use. Bona can only guarantee its products and not the construction as a whole. Observe recommendations from flooring manufacturer and the provisions of relevant standards.

2023-04-19

This data sheet replaces all previous versions, please check bona.com to ensure you have the latest version.